

PRODUCT DETAILS:

- Three lens options offer versatility in beam spread via an easy to remove and insert assemble includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- · Incorporates CREE LEDs with application performance tested by CREE
- Lamp adjustable +/- 20 degrees
- Optimal drive-over protection up to 4,500 lbs
- PVC constructed concrete pour kit and burial sleeve are supplied
- Includes a dense foam cap to prevent concrete from entering

WELL LIGHT

15702BZ-5W3K

LED 5W 3000K FLAT TOP

The LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the the user with full control over wattage and color temperature.

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	No

DIMENSIONS

DIMILINGIONS	
WIDTH:	4.5"
HEIGHT:	4"
DEPTH:	4.5
WEIGHT:	3lb

LIGHT SOURCE

h

LIGHT SOURCE:	LumaCore
LED NAME:	00G3SE-35
VOLTAGE:	12v
VOLT AMPS:	5.3
COLOR TEMP:	3000
LUMENS:	350
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 35w
DIMMABLE:	No
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 36"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5