

## PRODUCT DETAILS:

- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Lamp adjustable +/- 20 degrees
- PVC constructed concrete pour kit and burial sleeve are supplied
- Includes a dense foam cap to prevent concrete from entering
- Optional Hex Louver lens available (0037HL)

## **WELL LIGHT**

## 15705BZ-12W3K

LED 12W 3000K GRILL TOP

The LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the the user with full control over wattage and color temperature.

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	4.8"
HEIGHT:	4.8"
DEPTH:	4.8
WEIGHT:	3lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
LED NAME:	00G3SE-75
VOLTAGE:	12v
COLOR TEMP:	3000
LUMENS:	750
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w
DIMMABLE:	No
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 36"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539