

PRODUCT DETAILS:

- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Lamp adjustable +/- 20 degrees
- Optimal drive-over protection up to 4,500 lbs
- PVC constructed concrete pour kit and burial sleeve are supplied
- Includes a dense foam cap to prevent concrete from entering

WELL LIGHT

15702MZ-8W27K

LED 8W 2700K FLAT TOP

Named after the ruggedly beautiful island off the coast of British Columbia, Hardy Island products are impeccably designed to defy the harshest environments. The LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the the user with full control over wattage and color temperature.

| DETAILS | |
|-----------|--------------|
| FINISH: | Matte Bronze |
| MATERIAL: | Aluminum |
| GLASS: | Clear Lens |
| DIMMABLE: | No |

| DIMENSIONS | |
|------------|------|
| WIDTH: | 4.5" |
| HEIGHT: | 4" |
| DEPTH: | 4.5 |
| WEIGHT: | 3lb |

| LIGHT SOURCE | |
|------------------------------|-----------|
| LIGHT SOURCE: | LumaCore |
| LED NAME: | 27G3SE-50 |
| VOLTAGE: | 12v |
| VOLT AMPS: | 7.8 |
| COLOR TEMP: | 2700 |
| LUMENS: | 475 |
| CRI: | 80 |
| INCANDESCENT EQUIVALENCY: | 1 x 45w |
| DIMMABLE: | No |
| TRANSFORMER REQUIRED: | Yes |

| MOUNTING | |
|------------|---------|
| LEAD WIRE: | 1 X 36" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 7 |
| CARTON WIDTH: | 7 |
| CARTON HEIGHT: | 13.5 |
| CARTON WEIGHT: | 4.5 |



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539