

**GALERIE**  
COLLECTION



**LINK OFF WHITE**

**41906BN**

**SMALL SEMI-FLUSH MOUNT**

Perfected by its prominent round or square finial, Link represents an updated design suitable for all types of rooms. Its shade comes in Off White Linen or Heather Gray Linen, complemented by a Black or Brushed Nickel color combinations to enhance its chic silhouette.

| DETAILS   |   |
|-----------|---|
| FINISH:   | Brushed Nickel                          |
| MATERIAL: | Steel                                   |
| SHADE:    | Off-White Linen                         |
| DIMMABLE: | YES - WITH DIMMABLE LAMP (NOT INCLUDED) |

| DIMENSIONS |       |
|------------|-------|
| WIDTH:     | 13"   |
| HEIGHT:    | 11.5" |
| WEIGHT:    | 3lb   |

| LIGHT SOURCE  |                |
|---------------|----------------|
| LIGHT SOURCE: | Socketed       |
| WATTAGE:      | 2-17w Med. LED |
| VOLTAGE:      | 120v           |

| MOUNTING |            |
|----------|------------|
| CANOPY:  | 4.75" Dia. |

| SHIPPING       |      |
|----------------|------|
| CARTON LENGTH: | 15.5 |
| CARTON WIDTH:  | 11   |
| CARTON HEIGHT: | 16   |
| CARTON WEIGHT: | 4.9  |

**PRODUCT DETAILS:**

- Suitable for use in dry (indoor) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards.
- Classic, elegant lines and timeless details enhance a traditional space
- Merging modern and classic elements, the Galerie collection offers a selection of LED ceiling and sconce fixtures with unique details that effortlessly balance a variety of spaces with form and function. The complementary contours, materials and finishes allow each silhouette to be used in unison or easily combined with other Galerie pieces.
- Shade has three-prong mount resting on lower diffuser allowing easy tip-off, no tool lamp change. Fixture design promotes natural convection to extend LED lamp life.
- Diffusers are made of high transmittance, high diffusion, color stable LDA-filled polycarbonate to maximize delivered lumens